



# APD 25 A

Aksa  
Aksa  
P 602

Manufacturer		Aksa															
Model		A4CRX25															
		<table border="1"> <tr> <td>∅</td> <td>\$</td> <td>'</td> <td>"#</td> <td>"</td> </tr> <tr> <td>&amp;</td> <td>(</td> <td>z</td> <td>\$</td> <td>'</td> </tr> <tr> <td>0</td> <td>&amp;</td> <td>z</td> <td>\$</td> <td>&lt;DQ</td> </tr> </table>	∅	\$	'	"#	"	&	(	z	\$	'	0	&	z	\$	<DQ
∅	\$	'	"#	"													
&	(	z	\$	'													
0	&	z	\$	<DQ													
	L	2,540															
	"	90 X 100															
		18.0:1															
	fl # 7	"# "															
	L	8,50															
	L	11,00															
AbsorbedAirDischargeReSourceKey.Text	' # "	1,90															
fl ' # 7	' # "	113,00															
	' # "	5,00															
	° C	480,00															
		12 V d.c.															
	Load	∅\$ \$i															
	# "																
		5,50															

		Aksa
		AK218
	Hz	50
	"	22,50
7cg'		0,80
		3
	fl 7	400/230
	A	32,00

		fl 7		fl 7	
	"	"	"	"	L
APD 25 A	665,00	1500,00	900,00	1060,00	95,00
		fl 7		fl 7	
	"	"	"	"	L
ASM 3	790,00	1940	970	1220	95



# APD 25 A

Aksa  
Aksa P 602

9B: 49  
9b[ ]bY'gdYYX"  
C]'dfYggi fY"  
7cc'UbhY'a dYfUhi fY"  
F i b' hja Y"  
6UHYfmj c'rg"  
7cbZ[ i fUVY' hja ]b[ "  
; 9B9F 5HCF  
J c' hU[ Y f@ @B' "  
7i ffYbhf@&!@ E"  
: fYei YbVW"  
A 5-BG  
J c' hU[ Y f@ @B' "  
: fYei YbVW"  
A U]bg'fYUXn"  
A U]bg'YbUV'YX"  
; Yb"GYhfYUXn"  
; Yb"GYhYbUV'YX"

K 5F B-B;  
7\Uf[Y Z]i fY"  
6UHYfm@ck #][ \ ] c' hU[ Y"  
: U] 'hc' ghcd"  
@ck #][ \ [ YbYfUhc'f] c' hU[ Y"  
I bXYf#j Yf[ YbYfUhc'f] fYei YbVW"  
Cj Yf# bXYf'gdYYX"  
@ck c]'dfYggi fY"  
<][ \ V'c'UbhY'a dYfUhi fY"  
G<I H8CK BG  
: U] 'hc' ghUf"  
9a Yf[ YbVW'ghcd"  
@ck c]'dfYggi fY"  
<][ \ V'c'UbhY'a dYfUhi fY"  
Cj Yf# bXYf'gdYYX"  
I bXYf#j Yf[ YbYfUhc'f] fYei YbVW"  
I bXYf#j Yf[ YbYfUhc'f] c' hU[ Y"  
C]'dfYggi fY'gYbgcf'cdYb"  
7cc'UbhY'a dYfUhi fY'gYbgcf'cdYb"  
9@97 HF =75@HF -D  
: YbYfUhc'f] YfW'ffYbh"

: 'Yi ]V'Y'gYbgcf'WVb VY V'c'UbhY'a dYfUhi fY'Z  
dfYggi fY'Z dYfVW'bhU[ Y f'k Ufb]b[ #]i f'Xck b# 'YVW'VW' f'f'dL  
@c'WV'gYh]b[ 'dUfUa YHfg'UbX'a cb]hc'f]b[ 'Zca 'D7 'hc  
V'c'UbhY'a cXi 'Y'k ]h' I G6 V'c'UbhY'a dYfUhi fY'Z

9'YVW'VW' 'GUZYfm#9A 7 'V'c'UbhY'a dYfUhi fY'Z  
9'YVW'VW' 'Vi g]bYgg' 'Yei ]da Ybh'  
6G'9B '\*%\$#!\*!&9A 7 'ja a i b]mghUbxUfX"  
6G'9B '\*%\$#!\*!( '9A 7 'Ya ]gg]cb' ghUbxUfX"

'6UHYfmVWUf[ Yf ]g'a Ubi ZVW' fYX'k ]h' 'gk ]hVW]b[ !a cXY'UbX'GA 8 'fVW'bc'c[ mUbX'ih\Ug\ ][ \ YZ]VW'YVW' 6UHYfmVWUf[ Yf  
a cXY'gfci hdi hJ !=VWUfVW'f]gh]W]g] YfmV'cgY'hc'gei UfY'UbX'ci hdi h]g' ]'Ua dYfZ'% ž 'J 'Zcf'%&j c'hUbX'&+Z' 'J 'Zcf'&'( 'J '  
#bdi h% , ' !&\* ( 'j c'h57 "'Dfc]bY'&(\$) \Ug'Z 'mci hdi hg\chVW'VW]hdfchVW]cb'UbX'ihVWb VY i gYX'Ug'U'VW'ffYbhgci fVW"  
Dfc]bY'%&\$) #&(\$) VWUf[ Yf'\Ug'\ ][ \ YZ]VW'YVW'cb[ ' ]Z'Z' 'ck ZU]i fY'fUfY'Z' ][ \hk Y][ \hUbX'ck \YUhfUX]UfYX ]b  
UVW'cfXUbW'k ]h' ]bYUf'U'fYfbU]j Yg' H\Y'VWUf[ Yf ]g'Z]hYX'k ]h' U'dfchVW]cb X]cXY'UV'cgg'hY'ci hdi h'7 cbbYVW'VWUf[ Y'Z]  
fY'UmV'c] VYhk Yyb'dcg]h]j Y'ci hdi hUbX'7: 'ci hdi h' H\Y'mUfY'Yei ]ddYX'k ]h' F: =Z]fYf'hc' fYXi VV'Y'YVW'VW'bc]gY'fUX]UfYX  
Zca 'hY'XYj ]VW'; Uj Ub]VW' m]gc'UfYX ]bdi hUbX'ci hdi h]m]VW'm(\_J 'Zcf'\ ][ \ fY' ]UV] ]m'

# APD 25 A

Aksa  
Aksa P 602

## 5GA " !'



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 Base frame -fuel tank.
- 9 Lifting Points.
- 10 sound proofing materials.

## 1

	"	970
fl "L	"	1940
fl "L	"	1220
	L	95